



Series S1 impact wrench 1/2", ATEX 1148-ATEX

SAM Outillage 10 rue Camille de Rochetaillée 42000 Saint-Etienne - France RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

https://www.sam-outillage.com/

Photos and texts not contractually binding. Do not litter. Document generated on 2024-05-09 12:04:41





1/3





DESCRIPTION

Series S1 impact wrench 1/2", ATEX

POWERFULThe power developed represents an improvement of at least 25% with respect to what commonly exists for 1/2" wrenches.Compact wrench for intensive maintenance jobs, and also for automotive applications: exhaust, drivetrain.. Low-consumption wrench. Double-hammer punch, reducing the vibrations. Cold-insulating S1 casing (handhold and wrench balancing...).3-Position variable torque control and sensitive-touch control button at the front. Suspension ring.The Atex regulation (Explosive Atmospheres) stems from two European directives (ATEX directive 94/9/EC for equipment and 1999/92/EC for human safety).The ATEX directive (2014/34/EU) has been compulsory since 20/4/2016 and is tending to become the baseline in terms of safety, even outside the EU. (zones 11, 12, 21 and 22)

STANDARDS / DIRECTIVES

2006/42/CE, 2014/34/UE

Photos and texts not contractually binding. Do not litter. Document generated on 2024-05-09 12:04:41



LRQ/\

CERTIFIED

ISO 9001



SPECIFIC DATA

Designation	IMPACT WRENCH 1/2" ATEX
Sales reference	1148-ATEX
L (mm)	165
Weight (g)	2020
l (mm)	67
H (mm)	205
drive square	1/2"
Rotation speed (rpm)	6500
Noise level (dBa)	6.7
C mm	85
C min mm	6.5
C mm	170
Maximum input torque Nm	1/4"
Guarantee	1350

M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

>> Find out more





LRQ/\

CERTIFIED

ISO 9001