



Orbital sander, backing pad 150mm-2.5-nv 1342SP









DESCRIPTION

Orbital sander, backing pad 150mm-2.5-nv

ERGONOMIC In order to take tendinitis and musculo-skeletal disorders into account this series benefits from a special design (see page 42). Its profile also makes it possible to have a perfect view of the backing pad making the operator's work easier. PRECISE Its low height ensures excellent control of the backing pad's contact. INNOVATIVE Model 1448 is available as a 'dry air' version for users who work in surroundings where it is not permitted to use any grease or when it is essential that the treated surface should not be deteriorated. Sander made of composite material designed for finishing works. Its cooling system increases the tool's service life. Its low vibration level (1.5 m/s²) authorises prolonged utilisation. Lightweight (less than one kilo), equipped with a variable speed control. Exhaust on silencer.

STANDARDS / DIRECTIVES

2006/42/CE, ISO 11148-6, ISO 15744, ISO 28927-2

SAM Outillage

10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in









SPECIFIC DATA

Designation	NON VENTILATED ORBITAL SANDER 150MM-2.5
Sales reference	1342SP
L (mm)	190
Weight (g)	1170
I (mm)	150
h (mm)	84
Power (W)	200
Rotation speed (rpm)	12000
Noise level (dBa)	2.8
C mm	88
C min mm	6
C mm	150
Guarantee	1/4"

Guarantee applied

M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

>> Find out more



10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in





