



Orbital sander, backing pad 75mm-2.5-cv 1427P









DESCRIPTION

Orbital sander, backing pad 75mm-2.5-cv

RELIABLE This series of 75 mm orbital sanders combines three technical aspects that ensure great reliability and a longer tool lifetime: Very sensitive control lever, ensuring less jolting which lengthens the lifetime. Sander well-suited to touching up jobs and for operations on small surfaces. Its special design allows you to use it not only on irregular surfaces but also on areas with a rounded shape. The 2.5 mm models can also be used for the renovation of headlights. Ergonomic profile. Variable speed control. Rear exhaust on silencer block. With this reference the diameter of the coupler must be limited to 22mm.

STANDARDS / DIRECTIVES

2006/42/CE, ISO 11148-6, ISO 15744, ISO 28927-2

SAM Outillage

10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in









SPECIFIC DATA

Designation	ORBITAL SANDER 75 MM-2.5 - VENTILATION UNIT
Sales reference	1427P
L (mm)	135
Weight (g)	880
I (mm)	77
h (mm)	84
Power (W)	240
Rotation speed (rpm)	12000
Noise level (dBa)	1.9
C mm	81
C min mm	6.3
C mm	360
Guarantee	1/4"

Guarantee applied

M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

>> Find out more



10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in





