



# Mono complete sanding station with orbital sander model 1441

1468-1441









#### **DESCRIPTION**

# Mono complete sanding station with orbital sander model 1441

This new tool trolley is equipped with a filterless cyclone system which avoids clogging and greatly facilitates its maintenance. Its 1500 Watt by-pass motor can thus deliver optimum suction power as its air flow is no longer hindered but, on the contrary, is accelerated. However it is protected by a water-washable filter cartridge. It has an automatic starter system with all pneumatic sanders. Its upper part is fitted out to house the sander, abrasives and pipes. This layout is designed to avoid damaging bodywork. - Electrical power supply: 220/240 Volts - Cable length: 8 metres- Manual or automatic operation when the sander is started up. - Motor power: 1,500 W- Motor protected by filter cartridge - Air flow: 60L/s - Negative pressure: 3200 mm - Air supply: 7 bar / flow rate: 500 l/mm- Quick air connector installed - Cyclone column with micro-dust tank - Tank capacity: 50 l - Height: 1,300 mm - Diameter: 400 mm - Weight: 32 kg

## STANDARDS / DIRECTIVES

2006/42/CE, ISO 11148-6, ISO 15744, ISO 28927-2

# **SAM Outillage**

10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583  $\in$ 









## **SPECIFIC DATA**

Designation	VACUUM CLEANER WITH SANDER 1441
Sales reference	1468-1441
Weight (kg)	32.000
Guarantee	M1   SAM Equipment and Machine Guarantee:

#### **Guarantee applied**

#### M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

>> Find out more

10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583  $\in$ 





