



Digital inflator

1894

10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in











DESCRIPTION

Digital inflator

For inflating and checking the pressure. Digital display - High performance from low pressure to HGVs.- Technology:- Pressure range from 0.10 bar to 11 bar- 0.01 bar resolution - Utilisation temperature: -10°C to +40°C- Easy to read thanks to the 12 mm high digits, smaller display of last digit- Visual check of correct functioning of the digits each time pressure is applied- Product available with different measurement units (bar, psi*, kPa*)- Pressure gauge switches on automatically when pressure is applied (connection to the valve)- Switches off automatically when pressure is removed or when pressure is constant for more than 10 seconds- Battery lifetime: 10 years after manufacture in temperate surroundings (the battery cannot be replaced)-Automatic zeroing at each inflation to ensure there is no drift in the measurements- Display of the pressure measurements when the buttons are released- User alerted in case of failure- Design - Robustness:- Tried and tested design of the Univ'Air and Eurodainu pressure inflators- Air inlet tube F G 1/4- Elastomer protection encasing the measurement system.- Reinforced sealing by installation of clip-on slide- Very great measurement precision and level of precision maintained in case of impact on the device- Robustness: top-of-the-range thermoplastic components- Anti-pinching handle- Corrosion-resistant thanks to internal mechanism made of appropriate materials- Air filtering in the indicator mechanism by stainless steel and nickel-silver micro-porous filter- Device resistant to accidental 15 bar overpressure

SAM Outillage

10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in









STANDARDS / DIRECTIVES

86/217/CE, NFR 63-302

SPECIFIC DATA

Designation	DIGITAL INFLATOR 6.3 BAR CONNECTION 1/4"
Sales reference	1894
L (mm)	100
Weight (g)	820
I (mm)	100
h (mm)	240
C mm	6,3
C mm	1/4"
Inner pipe diameter mm	1
Guarantee	M1 SAM Equipment and Machine Guarantee:

Guarantee applied

M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

>> Find out more



10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in





