



Hollow punch for installing reversing radar

627-EMP

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-24 10:12:09





DESCRIPTION

Hollow punch for installing reversing radar

This kit is designed for installing reversing radar detectors on front and rear bumpers for all types of vehicle. You just have to make a \varnothing 8.5 mm pre-drilling, you will obtain a hole that does not need deburring and does not damage the paint, which allows you to retrofit a parking kit or repair a damaged vehicle. Specially developed quenched steel ensures sharp cutting and very good resistance. 13mm hex-head 8 mm screw. In a kit or individually so you can acquire just what you need. Utilisation: With a drill bit dia. 8.5 mm, make a hole at the chosen place. The part with the interior thread is positioned inside the bumper. The sliding die cutter on the screw must be inserted outside the bumper. Then use the punch with the appropriate size and then a manual ratchet wrench or a pneumatic machine (socket 13).

SPECIFIC DATA

Designation	HOLLOW PUNCH FOR INSTALLING REVERSING RADAR
Sales reference	627-EMP

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>



Weight (g)	720
Guarantee	C Consumable

Guarantee applied**C | Consumable**

The products in this category will not be replaced and are subject to normal wear phenomena.

[>> Find out more](#)

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-24 10:12:09

