



## DYNALIGHT® electronic torque wrenches, torque + angle

**DYCA-...**

### SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-26 00:15:01





## DESCRIPTION



## DYNALIGHT® electronic torque wrenches, torque + angle

EASY ACCESS TO THE TIGHTENING POINTS: thanks to ratchet that can be tilted to 15°. TIGHTENING OF SCREWS WITH RIGHT- OR LEFT-HAND PITCH: The wrench can be used in tightening or loosening mode. A SINGLE WRENCH: enabling tightening to the torque value and at the angle. INTUITIVE FAST SETTING OF THE TORQUE AND ANGLE: thanks to the integrated display.

Key to make tightening with great precision to the torque and the angle while guaranteeing total traceability.  
Ideal for automotive mechanical maintenance interventions.

### PRECISION

Accuracy guaranteed at +/- 2% in tightening and loosening mode.

### SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-26 00:15:01



Accuracy guaranteed at +/- 2% in angle tightening mode.  
Key supplied with 3-point calibration certificate and delivered in a box.

**COMFORT**

- Unit of tightening torque: Nm, Ft.lb, cm.kg, in.lb.
- Data exploitation with SAM-DYCA software.
- Connectivity with USB cable supplied with the key.
- Memory capacity: 999 values.
- Zeroing of the key automatically at startup.
- Works with 2 x AA LR6 batteries supplied with the key.
- Handle resistant to hydrocarbons, solvents, brake fluid and oil.
- Measuring mode: peak.

**SAM DYCA Software**

- Exploitation of the data with the software.
- Save the data to a computer.
- The software is delivered with the key on a USB key.

Each key is numbered and delivered with a verification report in accordance with the NF EN ISO 6789 standard.  
Visual and audible alarm.  
Type I - Class C.

**STANDARDS / DIRECTIVES**

NF ISO 3315, NF ISO 6789-1

**SPECIFIC DATA**

Sales reference	L (mm)	Weight (kg)	Container	Capacity (Nm)	Ratchet	Capacity (Ft.lb)	Dimensions containing (mm)	Guarantee
DYCA-340-1  (not marketed)	664	2.62	Box	34 - 340	1/2	25,1 - 251	804 x 110 x 63	M

**SAM Outillage**

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France  
RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €  
<https://www.sam-outillage.com/>



DYCA-135-1	460	1.96	Box	13.5 - 135	3/8	9,96 - 99,6	492 x 110 x 63	M
------------	-----	------	-----	------------	-----	-------------	----------------	---

**Guarantee applied****M1 | SAM Equipment and Machine Guarantee:**

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

[>> Find out more](#)

**SAM Outillage**

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-26 00:15:01

