



DYNALIGHT® c electronic torque wrenches for rectangular ends

DYG-...

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-26 05:08:15





DESCRIPTION

DYNALIGHT® c electronic torque wrenches for rectangular ends

TIGHTENING OF SCREWS WITH RIGHT- OR LEFT-HAND PITCH: tightening or loosening mode. INTUITIVE FAST SETTING OF THE TORQUE AND ANGLE: thanks to the integrated display. CONNECTIVITY: Mini USB cable supplied.

The technological advances made over the past few years have allowed us to design increasingly precise torque wrenches thanks to the miniaturisation of the embedded electronics. This need for great precision can be seen in certain sectors of activity such as design offices, precision mechanics or quite simply for users who need traceability with a recording of their data.

Key to make tightening with great precision to the torque while guaranteeing total traceability.

Ideal for automotive mechanical maintenance interventions.

PRECISION

Accuracy guaranteed at +/- 2% in tightening and loosening mode.

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>



Key supplied with 3-point calibration certificate and delivered in a box.

COMFORT

Unit of tightening torque: Nm, Ft.lb, cm.kg, in.lb.

Memory capacity: 999 values.

Zeroing of the key automatically at startup.

Works with 2 x AA LR6 batteries supplied with the key.

Handle resistant to hydrocarbons, solvents, brake fluid and oil.

Measuring mode: peak.

Each key is numbered and delivered with a verification report in accordance with the NF EN ISO 6789 standard.

Visual and audible alarm.

Type I - Class C.

STANDARDS / DIRECTIVES

NF ISO 6789-1

SPECIFIC DATA

Sales reference	Weight (kg)	Container	Capacity (Nm)	Ratchet	Capacity (Ft.lb)	Ends	only wrench length	Length with ratchet (mm)	Ratchet reference	Dimensions containing (mm)	Guarantee
DYG-30-1 (not marketed)	1.75	Box	3 - 30	1/4	2,2 - 22	9 x 12	410	442	DTC0-R	492 x 110 x 63	M
DYG-340-0	2.4	Box	34 - 340	-	25,1 - 251	14 x 18	623	-	-	804 x 110 x 63	M

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>



DYG-200-0 (not marketed)	1.83	Box	20 - 200	-	14,8 - 148	14 x 18	470	-	-	660 x 110 x 63	M
DYG-135-0 (not marketed)	2.42	Box	13.5 - 135	-	9,9 - 99,6	9 x 12	410	-	-	492 x 110 x 63	M
DYG-30-0	1.68	Box	3 - 30	-	2,2 - 22	9 x 12	410	-	-	492 x 110 x 63	
DYG-135-1 (not marketed)	1.86	Box	13.5 - 135	3/8	9,9 - 99,6	9 x 12	410	450	DTC0-J	492 x 110 x 63	M
DYG-340-1	2.72	Box	34 - 340	1/2	25,1 - 251	14 x 18	623	670	DTC-S-350	804 x 110 x 63	M
DYG-200-1 (not marketed)	2.17	Box	20 - 200	1/2	14,8 - 148	14 x 18	470	515	DTC-S	660 x 110 x 63	M

Guarantee applied

M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

[>> Find out more](#)

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

