



DYNASAM® 4.0 communicating low-torque wrench 1-10 nm

DYMSC-10-1

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-29 17:54:27





DESCRIPTION

DYNASAM® 4.0 communicating low-torque wrench 1-10 nm

PLUG & PLAY: INTERACTIONS WITH YOUR NETWORK

- configuration, setting and utilisation operations guaranteed in real time.
- WiFi connectivity: 2.4 GHz – 5 GHz (IEEE standard 802.11 a/b/g/n) enabling a maximum range in industrial surroundings.
WiFi customisable to meet your network requirements: hostName, Ip, Port...
- Possibility of integrating a security certificate (EAP-TLS) guaranteeing the inviolability of your exchanges.

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-29 17:54:27



- Open SAM protocol functioning on TCP/IP Socket with detailed procedure SAM Tools Commands (ASCII format).

SECURED PROCESS: TOTAL TRACEABILITY

- Made-to-measure recording and continuous control of your operations, results and events according to your process.
- Measurement modes available to guarantee your tightening operations: Torque, Angle, Torque + angle.
- Controlled adjustment from the interface only: no risk of operator error.
- Configuring of your wrench's last calibration and/or verification date.

IMMEDIATE IMPLEMENTATION: EASE OF USE

- Independent measurement of your hand's position
- Visual and sensory indicators to inform the operator that the torque value has been reached.
- Wrench battery life: 8h.
- Memory kept when changing the battery.
- Reduced weight and dimensions.
- Tools and accessories supplied in a dedicated box.

DYNASAM 4.0 FRENCH KNOW-HOW IN ELECTRONICS, MECHANICS AND IT.

Double-alert bargraph with customisable user tolerance + 3 coloured visual markers:

- Orange: tightening in progress
- Green: tightening conform
- Red: tightening non-conform.

Tightening values guaranteed thanks to the three alert levels: visual, aural and sensory.

Follower measurement precision: +/- 2%.

Wrench supplied with a 3-point calibration certificate conform to standard NF EN ISO 6789-1 (2017).

Wrench available with or without the dedicated application, to meet your needs:

- DYMSC-...-1: Includes a wrench, 2 end fittings 1/4" and 3/8" + 2 batteries with charger.
- DYMC-...-2: Same contents + smartphone + dedicated application.

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>



STANDARDS / DIRECTIVES

NF ISO 3315, NF ISO 6789-1

SPECIFIC DATA

Designation	DYNASAM BOX LOW TORQUES 1-10 NM
Sales reference	DYMSC-10-1
Weight (kg)	2.28
Container	Box
Capacity (Nm)	1-10
Ratchet	1/4 + 3/8
double square	-
Graduation (Nm)	0,1
Ends	9x12 mm
only wrench length	230
Length with ratchet (mm)	
Ratchet reference	DTC0-R , DTC0-J
Dimensions containing (mm)	90x280x425
Guarantee	M1 SAM Equipment and Machine Guarantee:

Guarantee applied

M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

>> [Find out more](#)

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-29 17:54:27

