



## DYNASAM® 4.0 communicating low-torque wrench 0.4-4 nm

**DYMSC-4-1**

### SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-09 20:23:54





## DESCRIPTION

### DYNASAM® 4.0 communicating low-torque wrench 0.4-4 nm

PLUG & PLAY: INTERACTIONS WITH YOUR NETWORK› configuration, setting and utilisation operations guaranteed in real time.› WiFi connectivity: 2.4 GHz – 5 GHz (IEEE standard 802.11 a/b/g/n) enabling a maximum range in industrial surroundings.› WiFi customisable to meet your network requirements: hostName, Ip, Port...› Possibility of integrating a security certificate (EAP-TLS) guaranteeing the inviolability of your exchanges.› Open SAM protocol functioning on TCP/IP Socket with detailed procedure SAM Tools Commands (ASCII format).SECURED PROCESS: TOTAL TRACEABILITY› Made-to-measure recording and continuous control of your operations, results and events according to your process.› Measurement modes available to guarantee your tightening operations: Torque, Angle, Torque + angle.› Controlled adjustment from the interface only: no risk of operator error.› Configuring of your wrench's last calibration and/or verification date.IMMEDIATE

#### SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-09 20:23:54



IMPLEMENTATION: EASE OF USE › Independent measurement of your hand's position › Visual and sensory indicators to inform the operator that the torque value has been reached. › Wrench battery life: 8h. › Memory kept when changing the battery. › Reduced weight and dimensions. › Tools and accessories supplied in a dedicated box.

DYNASAM 4.0 FRENCH KNOW-HOW IN ELECTRONICS, MECHANICS AND IT. Double-alert bargraph with customisable user tolerance + 3 coloured visual markers:- Orange: tightening in progress- Green: tightening conform- Red: tightening non-conform. Tightening values guaranteed thanks to the three alert levels: visual, aural and sensory. Follower measurement precision: +/- 2%. Wrench supplied with a 3-point calibration certificate conform to standard NF EN ISO 6789-1 (2017). Wrench available with or without the dedicated application, to meet your needs:- DYMSC-...-1: Includes a wrench, 2 end fittings 1/4" and 3/8" + 2 batteries with charger.- DYMC-...-2: Same contents + smartphone + dedicated application.

## STANDARDS / DIRECTIVES

NF ISO 3315, NF ISO 6789-1

## SPECIFIC DATA

Designation	DYNASAM BOX LOW TORQUES 0.4-4 NM
Sales reference	DYMSC-4-1
Weight (kg)	2.6
Container	Box
Capacity (Nm)	0.4-4
Ratchet	1/4 + 3/8
double square	-
Graduation (Nm)	0,1
Ends	9x12 mm
only wrench length	230
Length with ratchet (mm)	

## SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-09 20:23:54



Ratchet reference	DTC0-R , DTC0-J
Dimensions containing (mm)	90x280x425
Guarantee	M1   SAM Equipment and Machine Guarantee:

#### Guarantee applied

##### M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

[>> Find out more](#)

#### SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-09 20:23:54

