



DYNATECH® torque wrenches with removable ends

DYTC-50-0
DYTC-...-0

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>





DESCRIPTION



DYNATECH® torque wrenches with removable ends

GREATER PRODUCTIVITY: owing to a reduced immobilisation thanks to the high-strength ratchets.**AN ALL-STEEL WRENCH:** making it possible to withstand every type of working environment.**LIMITED CALIBRATION ERRORS:** via the setting with the easy-to-use vernier.**EASY TO READ WHATEVER THE CONDITIONS:** even in full sunlight thanks to the long-life black marking on the vernier.**EASY-TO-USE TOOL:** thanks to a direct, ergonomic grip.**EJECTION OF THE BITS WITH A PUSHBUTTON:** ensuring quick, easy changes.

Precise, multi-purpose wrench allowing you to perform a large number of interventions without having to change tool.Repeatability guaranteed to ensure the safety of your tightening operations. Wrench used for loosening by turning the end-piece around.Each wrench is numbered and supplied with a verification report in compliance with standard NF EN ISO 6789.Mechanical release wrench. Precision guaranteed to +/- 3% per standard ISO 6789.Type II - Class A.

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>



Versatile, precise wrench for performing multiple interventions without having to change tool. Repeatability guaranteed to ensure the safety of your tightening operations. Utilisation of the wrench for loosening by turning the end fitting over. ERGONOMIC: Handle that withstands hydrocarbons, solvents, brake fluid and paraffin. Efficient, comfortable grip for the operator, reducing risks of musculoskeletal disorders. COMFORT: Scale in Nm with utilisation range going from 1 to 1,000 Nm, allowing you to have the right tool whatever the situation. Wrench supplied with a 3-point calibration certificate in a plastic case or in a box depending on the number of accessories. PRECISION: Precision guaranteed to within +/- 3% for up to 5,000 cycles, i.e. 25% better than the requirements of standard ISO 6789-1 (except models with capacities of 1-5 Nm: +/- 6%). New spring withstanding 1,000,000-cycle fatigue tests at each wrench's max. torque value. Mark on the handle for perfect positioning of the contact point ensuring precise tightening. Each wrench is numbered and supplied with a verification report in compliance with standard NF EN ISO 6789. Mechanical click-type torque wrench. Type II - Class A.

STANDARDS / DIRECTIVES

NF ISO 3315, NF ISO 6789-1

SPECIFIC DATA

Designation	TORQUE WRENCH DYNATECH 50 NM FOR SQUARE ENDS
Sales reference	DYTC-50-0
Weight (kg)	1.100
Container	Tube
Capacity (Nm)	10-50
Ratchet	-
double square	-
Graduation (Nm)	0,5
Ends	9x12 mm
only wrench length	341

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>



Length with ratchet (mm)	-
Ratchet reference	-
Dimensions containing (mm)	350 x 45 x 45
Guarantee	M

Guarantee applied

M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

[>> Find out more](#)

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

