



DYNATECH® torque wrenches with fixed ratchet





10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in

https://www.sam-outillage.com/









DESCRIPTION



DYNATECH® torque wrenches with fixed ratchet

GREATER PRODUCTIVITY: owing to a reduced immobilisation thanks to the high-strength ratchets.AN ALL-STEEL WRENCH: making it possible to withstand every type of working environment.LIMITED CALIBRATION ERRORS: via the setting with the easy-to-use vernier.EASY TO READ WHATEVER THE CONDITIONS: even in full sunlight thanks to the long-life black marking on the vernier.EASY-TO-USE TOOL: thanks to a direct, ergonomic grip

Precise, multi-purpose wrench allowing you to perform a large number of interventions without having to change tool. Repeatability guaranteed to ensure the safety of your tightening operations. Each wrench is numbered and supplied with a verification report in compliance with standard NF EN ISO 6789. Mechanical release wrench. Precision guaranteed to +/- 3% per standard ISO 6789. Type II - Class A.

SAM Outillage

10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in









DYTF-5-1DYNATECH® torque wrenches with fixed ratchet

Versatile and precise key allowing to carry out multiple interventions without changing tools.

Repeatability guaranteed to ensure the safety of your tightenings.

ERGONOMICS:

Handle resistant to hydrocarbons, solvents, brake fluid and oil.

Efficient and comfortable grip for the operator reducing the risk of MSDs.

COMFORT:

Scale in Nm with wide range of use ranging from 1 to 350 Nm, to have the right tool for all possible situations.

Key supplied with a 3-point calibration certificate in a plastic case or case according to the number of accessories.

ACCURACY:

Accuracy guaranteed at +/- 3% up to 5000 cycles, 25% better than ISO 6789 (except models with 1-5Nm capacity: +/- 6%).

New spring enduring fatigue tests of 1,000,000 cycles to the maximum torque of each key.

Mark on the handle for a perfect positioning of the point of support ensuring accurate tightening.

Each key is numbered and delivered with a verification report in accordance with the NF EN ISO 6789 standard.

Mechanical key with trigger.

Type II - Class A.

STANDARDS / DIRECTIVES

NF ISO 3315, NF ISO 6789-1


SPECIFIC DATA

Designation	TORQUE WRENCH KIT DYNATECH 5 NM FOR ROUND ENDS
Sales reference	DYTF-5-1
L (mm)	198
Weight (kg)	0.41
Container	Tube

SAM Outillage

10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in









Capacity (Nm)	1-5
Ratchet	1/4
Graduation (Nm)	0,05
Dimensions containing (mm)	260 x 35 x 35
Guarantee	М

Guarantee applied

M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

>> Find out more

10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in





