



Open steel frame air hose reel

ENR-AC10-18

ENR-AC...

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-18 09:50:04





DESCRIPTION

Open steel frame air hose reel

Air hose winder with open steel chassis.

Special high-strength plastic reel

Zinc-plated steel support bracket avoiding corrosion.

Indicated for several types of attachment installations (floor, ceiling, wall). Ratchet for stopping the hose at the desired length, easily retractable if the hose is continuously used unreeled.

Soft plastic end-of-course blocking ball.

Pure polyurethane hose.

Brass/stainless steel joint pivoting through 360° preventing leaks and hyper-resistant to repeated cycles.

Used to direct the pressure.

Utilisation temperature from -5°C to 50°C.

ENR-AC-10-18: outer dia. 14 mm, inner dia. 10 mm, min. bending radius 60 mm, weight 1.1 kg/m and hose length 18m

ENR-AC-13-15: outer dia. 17.5 mm, inner dia. 125 mm, min. bending radius 75 mm, weight 1.6 kg/m and hose length 15m.

Max. service pressure 20 bar, burst pressure 60 bar.

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>



STANDARDS / DIRECTIVES

EN 12100-1, EN 12100-2

SPECIFIC DATA

Designation	AIRPIPE REEL OPEN STEEL FRAME 10 MM - 18M
Sales reference	ENR-AC10-18
Weight (kg)	13.2
Guarantee	M

Guarantee applied**M1 | SAM Equipment and Machine Guarantee:**

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

[>> Find out more](#)**SAM Outillage**10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>