



2 and 3-arm self-centring extractor

EX-220-6 EX-220...







https://www.sam-outillage.com/ Photos and texts not contractually binding. Do not litter. Document generated on 2024-05-03 21:22:49







DESCRIPTION



2 and 3-arm self-centring extractor

SAFETY: The claws do not open more than recommended.COMFORT: Fitted with an O-ring limiting the absorption of the impact generated by the great forces.PRACTICAL: Self-centred, adjustable height.

Self-centring pullers with simultaneous claw movement, enabling quick, easy installation and balanced positioning for optimum distribution of the forces.Fitted with an O-ring that absorbs the impact generated by the great forces applied.On references EX-220-6 and 7, the body of the puller has a bronze nut allowing you to increase the traction force. Secure, it will not be possible to open the claws more than is recommended.



LRQ/\

CERTIFIED

ISO 9001




SAM Outillage 10 rue Camille de Rochetaillée 42000 Saint-Etienne - France RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 € https://www.sam-outillage.com/

Photos and texts not contractually binding. Do not litter. Document generated on 2024-05-03 21:22:49



SPECIFIC DATA



Designation	2 AND 3-ARM SELF-CENTRING EXTRACTOR
Sales reference	EX-220-6
Weight (kg)	55.500
A (mm)	600
Power T	30
B (mm)	650
Guarantee	0

Guarantee applied

O | SAM TOOL guarantee.

Guarantee without time limit on the tools used under normal conditions.

>> Find out more





