



Single torque clutchable torque wrenches with fixed ratchet

MC-...-RC

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-27 08:02:34





DESCRIPTION



Single torque clutchable torque wrenches with fixed ratchet

IMPOSSIBLE TO EXCEED THE TORQUE VALUE: thanks to the ratchet disengagement system. ROBUST WRENCH: designed for production environments. COMFORTABLE TO USE: with a light weight thanks to the aluminium body. IMPOSSIBLE FOR THE OPERATOR TO CHANGE THE TORQUE VALUE: there is no adjustment vernier.

Torque wrench that prevents overtightening, dedicated to production and repetitive tightening operations. Disengageable mechanical release system. ERGONOMIC: Handle that withstands hydrocarbons, solvents, brake fluids and paraffin. Made of aluminium to reduce weight and therefore risks of musculo-skeletal disorders. Fixed ratchet head with 1/4" to 1/2" square. PRECISION: Precision guaranteed to +/- 4% (except MC-10-RC: +/- 6%). Wrench supplied with one-point calibration certificate in a plastic case. Adjustment of the tightening torque by means of the SAM calibration bench (BC-5N + DYC-...N + DYB + DYT-KIT1). Type II - Class B.

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>



Torque wrench preventing over-tightening, dedicated to production and repetitive tightening jobs. Disengageable mechanical release system. ERGONOMY: Handle resistant to hydrocarbons, solvents, brake fluids and petroleum... Made of aluminium reducing the wrench's weight and therefore the risks of musculoskeletal disorders. Fixed ratchet head with 1/4" and 1/2" square. PRECISION: Precision guaranteed to +/- 4% (except MC-10-RC: +/- 6%). Wrench supplied with 1-point calibration certificate in a plastic case. Setting of the tightening torque with the SAM calibration bench (BC-5N + DYC-...N + DYB + DYT-KIT1). Type II - Class B. This is a single-torque value wrench, so please indicate your desired tightening value (Nm) when placing your order.

STANDARDS / DIRECTIVES

NF ISO 1174-1, NF ISO 3315, NF ISO 6789-1

SPECIFIC DATA

Sales reference	Weight (kg)	Capacity (Nm)	Ratchet	only wrench length	Length with ratchet (mm)	Guarantee
MC-10-RC	0.31	2-10	1/4	-	180	M
MC-125-RC	1.37	40-125	1/2	-	500	M
MC-50-RC	0.85	15-50	3/8	-	330	M
MC-25-RC	0.35	3-25	1/4	-	238	M

Guarantee applied

M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

>> [Find out more](#)

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

