



## Single torque clutchable torque wrenches with fixed ratchet

**MC-10-RC**  
MC-...-RC

### SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-05-08 01:17:12





## DESCRIPTION



## Single torque clutchable torque wrenches with fixed ratchet

**IMPOSSIBLE TO EXCEED THE TORQUE VALUE:** thanks to the ratchet disengagement system.**ROBUST WRENCH:** designed for production environments.**COMFORTABLE TO USE:** with a light weight thanks to the aluminium body.**IMPOSSIBLE FOR THE OPERATOR TO CHANGE THE TORQUE VALUE:** there is no adjustment vernier.

Torque wrench that prevents overtightening, dedicated to production and repetitive tightening operations. Disengageable mechanical release system. **ERGONOMIC:** Handle that withstands hydrocarbons, solvents, brake fluids and paraffin. Made of aluminium to reduce weight and therefore risks of musculo-skeletal disorders. Fixed ratchet head with 1/4" to 1/2" square. **PRECISION:** Precision guaranteed to +/- 4% (except MC-10-RC: +/- 6%). Wrench supplied with one-point calibration certificate in a plastic case. Adjustment of the tightening torque by means of the SAM calibration bench (BC-5N + DYC-...N + DYB + DYT-KIT1). Type II - Class B.

### SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-05-08 01:17:12



Torque wrench preventing over-tightening, dedicated to production and repetitive tightening jobs. Disengageable mechanical release system. **ERGONOMY:** Handle resistant to hydrocarbons, solvents, brake fluids and petroleum... Made of aluminium reducing the wrench's weight and therefore the risks of musculoskeletal disorders. Fixed ratchet head with 1/4" and 1/2" square. **PRECISION:** Precision guaranteed to +/- 4% (except MC-10-RC: +/- 6%). Wrench supplied with 1-point calibration certificate in a plastic case. Setting of the tightening torque with the SAM calibration bench (BC-5N + DYC-...N + DYB + DYT-KIT1). Type II - Class B. This is a single-torque value wrench, so please indicate your desired tightening value (Nm) when placing your order.

## STANDARDS / DIRECTIVES

NF ISO 1174-1, NF ISO 3315, NF ISO 6789-1

## SPECIFIC DATA

|                          |                                     |
|--------------------------|-------------------------------------|
| Designation              | CLUTCHABLE TORQUE WRENCH 2 TO 10 MM |
| Sales reference          | MC-10-RC                            |
| Weight (kg)              | 0.310                               |
| Capacity (Nm)            | 2-10                                |
| Ratchet                  | 1/4                                 |
| only wrench length       | -                                   |
| Length with ratchet (mm) | 180                                 |
| Guarantee                | M                                   |

### Guarantee applied

#### M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

[>> Find out more](#)

### SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-05-08 01:17:12

