



Pressure reducer for PEA cylinder - 20 bar PEA-DET20









DESCRIPTION

Pressure reducer for PEA cylinder - 20 bar

The regulator is the device that reduces the high pressure in the cylinder to a low outlet pressure ideal for the totally safe use of air-powered tools.

The regulator is the essential component that guarantees the PEA's performance for all your jobs.

Outlet pressure: 6.5 bar

Nominal pressure: 400-500 l/min (300 at 40 bar)

Pressure gauge: 0-300 bar Meets standard EN ISO 2503

STRENGTH:

Resists extreme temperatures: -20°C to + 60°C

Resists excess pressures up to 350 bar

Shock-resistant

High wear resistance

PRACTICAL:

SAM Outillage

10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in









PEA-DET20Pressure reducer for PEA cylinder - 20 bar

Constant outlet pressure in the 300-40 bar range

The lightest and smallest cylinder on the market

Controlled, regulated flow

No loss of pressure

More reliable

SPECIFIC DATA

Designation	PEA 20 BAR PRESSURE REGULATOR WITH HOSE DIA. 13 MM X 5 M
Sales reference	PEA-DET20
Weight (g)	4140
Guarantee	M1 SAM Equipment and Machine Guarantee:

Guarantee applied

M1 | SAM Equipment and Machine Guarantee:

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

>> Find out more



10 rue Camille de Rochetaillée 42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 \in





