



1/2" pressure-regulating lubricator filter

PN-2102

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-25 06:44:08





DESCRIPTION

1/2" pressure-regulating lubricator filter

Body made of Zamak, metal tank. Supplied with a pressure gauge. Oil-mist lubrication. Tank filling is ensured automatically by negative pressure, the level is shown by an indicator integrated on the tank. Flow rate (l/min): 1550. Filtration (microns): 25. Utilisation pressure (bar): 0-18. Utilisation temperature (°C): 0-60. Pressure gauge diameter (mm): 50. Recommended oil: Engler viscosity at 50°C (1.95), aniline point (100). Weight: 2.4 kg.

SPECIFIC DATA

Designation	DRYER FILTER - LUBRICATOR 1/2"
Sales reference	PN-2102
Weight (kg)	2.36

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-25 06:44:08



H (mm)	224
I min (mm)	110
Guarantee	M1 SAM Equipment and Machine Guarantee:

Guarantee applied**M1 | SAM Equipment and Machine Guarantee:**

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

[>> Find out more](#)

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-25 06:44:08

