



Pressure-regulating lubricator filter with spacer

PN-2103

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-05-07 01:21:30





DESCRIPTION

Pressure-regulating lubricator filter with spacer

1/2" body made of Zamak, metal tank. Supplied with a pressure gauge. Oil-mist lubrication, but it is also possible to deliver non-lubricated air. Flow rate (l/min): 1550. Filtration (microns): 25. Utilisation pressure (bar): 0-18. Utilisation temperature (°C): 0-60. Pressure gauge diameter (mm): 50. Recommended oil: Engler viscosity at 50°C (1.95), aniline point (100). Weight: 2.5 kg.

SPECIFIC DATA

Designation	MANO.REGUL.LUBRI.FIL.&SPAC1/2"
Sales reference	PN-2103
Weight (kg)	2.875
H (mm)	224

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-05-07 01:21:30



I min (mm)	165
Guarantee	M1 SAM Equipment and Machine Guarantee:

Guarantee applied**M1 | SAM Equipment and Machine Guarantee:**

Guarantee for a limited period, covering technical tools, devices and machines used under normal conditions. The length is given by the number after the letter M: 1 to 5 years

[>> Find out more](#)

SAM Outillage

10 rue Camille de Rochetaillée
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-05-07 01:21:30

