



## DYNAMOVIS® screwdriver 3 to 5.4 nm - hexagonal blade

**T3DIN-H...**

### SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>





## DESCRIPTION

### DYNAMOVIS® screwdriver 3 to 5.4 nm - hexagonal blade

IMPOSSIBLE TO OVERSHOOT THE TORQUE VALUE: thanks to the torque limiting mechanism. MODULAR: Use the blade of your choice according to what you need with the same screwdriver. EASY TO SET: the tightening torque on the end of the screwdriver with a simple 6mm male key (supplied). IMMEDIATE IDENTIFICATION: Coloured ring identifying the tightening range.

DYNAMOVIS-3 screwdriver (3.0 to 5.4 Nm).

#### ACCURACY:

Accuracy guaranteed at +/- 6%.

Single-direction disengaged screwdriver, right-hand tightening.

No adjustment of the tightening torque possible by the operator.

Screwdriver numbered and delivered with a calibration certificate in accordance with NF EN ISO 6789.

Length (without blade): 157 mm.

#### SAM Outillage

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

Photos and texts not contractually binding. Do not litter. Document generated on 2024-04-24 16:21:35



Length (with blade): 193 mm.

Diameter: 33 mm.

Type II - Class D.

**STANDARDS / DIRECTIVES**

ISO 6789

**SPECIFIC DATA**

Sales reference	L (mm)	Weight (kg)	D (mm)	Capacity	drive	Guarantee
T3DIN-H3	193	0.205	33	3,0 - 5,4 Nm	1/4" 6-flat hollow-head wrench	O
T3DIN-H4 (not marketed)	193	0.2	33	3,0 - 5,4 Nm	1/4" 6-flat hollow-head wrench	O

**Guarantee applied**

**O | SAM TOOL guarantee.**

Guarantee without time limit on the tools used under normal conditions.

>> [Find out more](#)

**SAM Outillage**

10 rue Camille de Rochetaillée  
42000 Saint-Etienne - France

RCS Saint-Etienne B 338 002 231 | SAS au capital de 8 189 583 €

<https://www.sam-outillage.com/>

